WO 2005/015873 A1

## IAP20 Recidificities 30 JAN 2006

## MODIFIED CLAIMS

[received by the International Office on January 10, 2005(01.10.2005); claim 1 modified, claim 2 deleted, claims 3-15 renumbered 2-14 and modified]

## CLAIMS

- 1. A processing method for data exchanged between a portable object and an interface device, the portable object being of the chip card or chip key type, characterized in that the method comprises a protocol detection mode implemented within and by the portable object in which the following steps are planned:
  - a) After transmission of a response upon turning on the portable object, an initial signal is received from the interface device;
  - b) In the portable object, said initial signal is sampled according to at least one of the first and second speeds associated with the first and second respective protocols;
  - c) In the portable object, at least one sample of a resulting sampling signal is compared to at least one key protocol condition proper to one of the first and second protocols; and
  - d) According to the result of the comparison, the data exchanged according to one of the first or second communication protocols is processed in the portable object.
- 2. The method according to claim 1, characterized in that step b) consists of sampling said the initial signal according to the first speed or the second speed, corresponding respectively to the first and second

protocols, in that step c) consists of comparing at least one sample from the resulting sampling signal to a key condition proper to the first protocol, second of respectively, in case а positive comparison and according to the second protocol, first of protocol respectively, in case comparison.

- 3. The method according to any one of the previous claims, characterized in that the key protocol condition proper to the first protocol relates to the parity of the first bit of the first character.
- 4. The method according to claim 1, characterized in that the second protocol key to the second protocol relates to the value of the most significant bit of the first character.
- 5. The method according to claim 1, characterized in that the elementary time unit of the first speed is equal to 372/if, where "if" is the frequency provided by the interface device during the response to the portable object being turned on.
- 6. The method according to claim 1, characterized in that the elementary time unit of the first speed is equal to 396/if, where "if" is the frequency provided by the interface device during the response to the portable object being turned on.
- 7. The method according to any one of the previous claims, characterized in that the portable object is a chip card implementing both a protocol in conformance with ISO standard 7816-3 and a SYSTER (registered trademark) digital television protocol.

- A portable object able to exchange data with 8. interface device, the portable object being of the chip card or chip key type, characterized in that the portable object comprises means for processing able, after transmission of a response to the portable object being turned on, to receive from the interface device an initial signal; to sample said initial signal according to at least one of the first and second speeds associated with the first and second compare at protocols, to respective respective sample of said initial signal thus sampled according to at least the first and second speeds to at least the key protocol conditions proper to the first and second protocols respectively, and according to the result of the comparison, to process the data thus exchanged according to one of the first or second communication protocols.
- 9. The portable object according to claim 8, characterized in that the key condition proper to the first protocol relates to the parity of the first bit of the first character sampled at the speed in conformance with the standard.
- 10. The portable object according to claim 8, characterized in that the key condition proper to the second protocol relates to the value of the most significant bit of the first character read at the non-conforming speed.
- 11. The portable object according to claim 8, characterized in that the elementary time unit of the first speed in conformance is equal to 372/if, where "if" is the frequency provided by the interface device during the response to the portable object being turned on.

- 12. The portable object according to claim 8, characterized in that the elementary time unit of the second speed in conformance is equal to 396/if, where "if" is the frequency provided by the interface device during the response to the portable object being turned on.
- 13. The portable object according to any one of claims 9 to 12, characterized in that the portable object is a chip card implementing both a protocol in conformance with ISO standard 7816-3 and a SYSTER (registered trademark) digital television protocol.
- 14. A computer program stored on an information support, said program comprising instructions allowing the implementation of a processing method according to any one of claims 1 to 7, when this program is loaded and executed by a computer system.